




# Hard Floor Cleaning Program

## ROUTINE



### AUTO SCRUB OR DAMP MOP CLEANING




- AUTO SCRUB CLEANING**
- DUST MOP** the floor before applying cleaner.
  - DILUTE:** Mix product according to label directions.
  - CLEAN:** Scrub with red pad. Apply cleaning solution, scrub and pick up in one operation. Rinsing not required.
  - PICK UP TRAILS:** Use clean water and mop/bucket to pick up any trails left from autoscrubber.

- DAMP MOP CLEANING**
- DUST MOP** the floor before applying cleaner.
  - DILUTE:** Mix product according to label directions.
  - CLEAN:** Using a clean mop, damp mop the floor. Change the cleaning solution frequently. No rinse required.

## RESTORATION



### AUTO SCRUB OR DAMP MOP CLEANING




- AUTO SCRUB CLEANING**
- DUST MOP** the floor before applying cleaner.
  - DILUTE** product according to label directions.
  - APPLY** solution and scrub with a red or white pad. Vacuum up excess solution from floor.
  - BURNISH** the floor when the solution is thoroughly dry to "pop the gloss".

- DAMP MOP CLEANING**
- DUST MOP** the floor before applying cleaner.
  - DILUTE** product according to label directions.
  - APPLY** solution to floor. Change solution when it becomes dirty. No rinsing required.
  - BURNISH** the floor when the solution is thoroughly dry to "pop the gloss".

## SCRUB & RECOAT



### SCRUB & RECOAT




- DUST MOP** the floor. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife.
- DAMP MOP** or **AUTOSCRUB** using Fuller Cleaner and following the label directions.
- APPLY** a coat of Fuller Finish a clean mop.
- DRY** Allow 20-30 minutes drying time.
- APPLY** 2 coats. For best results allow adequate drying time between each coat.
- BURNISH** optional burnishing after last coat - wait 1 hour.

## STRIPPING & FINISHING



### STRIPPING AND FINISHING



- DILUTE** product according to label directions.
- APPLY** the diluted solution liberally with a mop on a small section.
- SCRUB** the floor using a rotary machine and a black pad.
- REMOVE** the remaining solution off the floor using a mop or wet vacuum.
- RINSE** the floor with clean water and remove using a mop or wet vacuum.
- APPLY** 2 coats of Fuller **Sealer** a clean mop.
- DRY** Allow 20-30 minutes drying time between coats.
- APPLY** 4 coats of Fuller **Finish**. For best results allow adequate drying time between each coat.
- BURNISH** after last coat - wait 1 hour. (optional)



Distributed By:

MSDS Fax Retrieval:  
**800-551-0101**

CHEMTREC Day or Night:  
**800-424-9300**

TECH HOTLINE:  
**800-810-4829**